

VTH2421FB/FW

IP Indoor Monitor





| Tachnical Specification | |
|-------------------------|-------------------------------------|
| Technical Specification | |
| Model | VTH2421FB/FW |
| System | |
| Main Processor | Embedded Micro Processor |
| Operation System | Embedded LINUX OS |
| Video | |
| Video Compression | H.264 |
| Audio | |
| Audio Compression | G.711 |
| Audio Input | All-direction Microphone |
| Audio Output | Built-in Loudspeaker |
| Bidirectional Talk | Support Dual-way Bidirectional talk |
| Display | |
| LCD Screen | 7" 1024x600, Capacitive |
| Operation Mode | |
| Input | Touch Screen |
| Interface | |
| Alarm In | 6 |
| Alarm Out | 1 |
| Network | |
| Ethernet | 10M/100Mbps Self-adaptive |
| Network Protocol | TCP/IP |

Features

- 7" TFT Capacitive touch screen, 1024x600
- IPC surveillance
- · Alarm integration
- High performance & Cost-effective















General

| Installation | Surface & Desktop |
|---------------------|------------------------|
| Power | DC 12V |
| Power Consumption | Standby ≤1W, Work ≤7W |
| Working Temperature | -10°C~+55°C |
| Relative Humidity | 10%~90%RH |
| Dimensions | 119.6mm×221.5mm×21.5mm |
| Weight | 0.35Kg |

Dimensions View Area





Application

