



KEY FEATURES

- IP video doorphone station for outdoors with 1.3MP camera
- 1 call button
- Mifare proximity reader
- Built in microphone and speaker
- Fast Ethernet
- Alarm: 4 in / 1 out
- IP65
- 12V DC
- PoC

RELATED PRODUCTS



HYU-558 HYU-558

IP VIDEO DOORPHONE STATION FOR OUTDOORS WITH 1.3MP CAMERA

FEATURES

- IP video doorphone station for small housing with 1 call button
- Linux OS
- Colorful IP camera of 1.3 MP
- 720P resolution (1280x720) at 25 fps
- Autoadaptive IR leds
- H.264
- Mifare proximity card reader
- Compatible with con RS-485 external readers (HYUNDAI protocol)
- Remote unlock via client software or app (requires interior console)
- Alarm tamper and alarm by magnetic contact supported
- G.711u
- Built in omnidirectional microphone and speaker
- 2 way audio with noise supresion and echo cancellation
- Ethernet: 10/100Mbps auto-adaptive
- Network protocols: TCP/IP and RTSP
- Alarm: 4 inputs / 1 outputs
- RS485 Half-Duplex port
- Metal case
- IP65
- Working temperature: -40° ~ +60°C
- Working RH: 10% ~ 90%
- Power supply: 12V DC
- Power supply by network cable up to 40 meters (requires HYU-560)
- Consumption: <12W
- Dimensions: 182 x 100 x 33 mm