

HYUNDAI NEXTGEN IP VIDEO INTERCOM STATION WITH 2MP FISHEYE CAMERA



**KEY FEATURES**

- HYUNDAI NEXTGEN IP video intercom station with 2MP fisheye camera
- Physical buttons Access control function
- It incorporates microphone and speaker
- Fast Ethernet 4 inputs / 2 alarm outputs
- 12V DC PoE

**FEATURES**

- 2 MP video intercom function
- Access control function
- Noise suppression and echo cancellation
- Low lighting
- Supports tamper alarm
- Fisheye camera with infrared lighting supplement
- Supports up to 8 submodules
- Tag Customization
- Easy to extend

**SPECS**

- Embedded MCU Processor
- Embedded Linux operating system
- Operational method using physical buttons
- 2 MP low illumination camera with IR illumination
- H.264 video compression
- Main stream resolution: 1080P (1920x1080)
- Secondary stream resolution: 720x480
- BLC backlight compensation
- Digital WDR
- DNR digital noise reduction
- 50 / 60Hz antiflicker
- Viewing angle: 180 ° (H), 96 ° (V)
- It incorporates omnidirectional microphone
- It incorporates speaker (> 85dB at 20 cm)
- G.711U audio compression
- 64Kbps audio compression ratio
- Noise suppression and echo cancellation
- 10 / 100Mbps Ethernet port autoadaptive
- Protocols: TCP / IP, RSTP
- Tamper alarm
- 1 connection module
- 4 tickets
- Debug interface
- 2 relay outputs (30V, 1A)
- Power: 12V DC
- Consumption: ≤10W
- Supports PoE (802.3af)
- Operating temperature of 40 ° C ~ + 55 ° C
- Operating humidity of 10% ~ 95%
- Dimensions: 99.8 (W) x 98 (H) x 43.9 mm
- Recessed or surface installation