

DS-7324/7332HGHI-SH Series HD-TVI DVR



Features and Functions


- Connectable to TVI and analog cameras;
- Support HIKVISION-C protocol for connecting camera over coax;
- Connectable to network cameras;
- Simultaneous HDMI and VGA outputs at up to 1920×1080p resolution;
- New GUI and supports starting record with one key;
- Redundant recording, holiday recording schedule configuration;
- Instant playback for assigned camera during multi-channel live view mode;
- Support up to 24/32-ch synchronous playback; and reverse playback for multi-channel;
- Smart playback to go through less effective information;
- Manual video quality diagnostics;
- Support VCA alarm (line crossing detection and intrusion detection);
- Customization of tags, searching and playing back by tags;
- Locking and unlocking record files;
- Support HDD quota and group management; different capacity can be assigned to different cameras under quota mode;
- Provide 4 SATA interfaces and 1 eSATA interface for record and backup;
- 1 self-adaptive 10M/100M/1000M network interface;
- Support access by EZVIZ Cloud P2P;
- Support Hikvision DDNS (Dynamic Domain Name System);
- Network detection function.



Specifications

Model		DS-7324HGHI-SH	DS-7332HGHI-SH
Video/ Audio input	Video compression	H.264	
	Analog and HD-TVI video input	24-ch	32-ch
		BNC interface (1.0Vp-p, 75 Ω)	
	Supported camera types	720p/25, 720p/30, 720p/50, 720p/60, 1080p/25, 1080p/30, CVBS	
	IP video input	8-ch (up to 32-ch)	8-ch (up to 32-ch)
		Up to 2MP resolution	
	Audio compression	G.711u	
Video/ Audio output	Audio input	4-ch, RCA (2.0 Vp-p, 1 KΩ)	
	Two-way audio in	1-ch, RCA (2.0 Vp-p, 1 KΩ)	
	HDMI / VGA output	1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz	
	Encoding resolution	Main stream: 1080p (non-real-time)/720p/WD1/VGA/4CIF/CIF	
		Sub-stream: WD1 (non-real-time)/4CIF (non-real-time)/CIF/QCIF/QVGA	
	Frame rate	Main stream: 1/16 fps to Real time frame rate	
		Sub-stream: 1/16 fps to Real time frame rate	
	Video bitrate	32 Kbps to 6 Mbps	
	Audio output	1-ch, RCA (Linear, 1KΩ)	
	Audio bitrate	64 Kbps	
	Dual-stream	Support	
	Stream type	Video, Video & Audio	
	Synchronous playback	24-ch	32-ch
Network management	Playback resolution	1080p/720p/VGA/WD1/4CIF/CIF/QVGA/QCIF	
	Remote connection	128	
Hard disk	Network protocols	TCP/IP, PPPoE, DHCP, EZVIZ Cloud P2P, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS	
	Type	4 SATA interfaces for 4 HDDs; 1 eSATA interface	
External interface	Capacity	Up to 6TB capacity for each disk	
	Network interface	1; 10M/100M/1000M self-adaptive Ethernet interface	
	Serial interface	RS-232, RS-485, Keyboard	
	USB port	3 × USB 2.0	
General	Alarm in / out	16/4	
	Power supply	100 to 240 VAC, 47 to 63 HZ	
	Consumption (without hard disks)	≤ 55W	≤ 65W
	Working temperature	-10°C to +55°C (14°F to 131°F)	
	Working humidity	10% to 90%	
	Chassis	19-inch rack-mounted 1.5U chassis	
	Dimensions (W × D × H)	445 × 390 × 70 mm (17.5 × 15.3 × 2.7 inch)	
	Weight (without hard disks)	≤ 5 Kg (11.0lb)	

Physical Interfaces



Index	Description	Index	Description
1	VIDEO IN	9	RS-485 Serial Interface, Keyboard Interface, ALARM IN and ALARM OUT
2	AUDIO IN, RCA Connector	10	100 to 240 VAC Power Input
3	USB Port	11	Power Switch
4	HDMI Interface	12	GND
5	VGA Interface	13	LINE IN
6	VGA AUDIO OUT	14	eSATA Interface
7	LAN Network Interface	15	RS-232 Serial Port
8	VIDEO IN		

Available Models

DS-7324HGHI-SH, DS-7332HGHI-SH.

Distributed by



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T +44-1628-9021-4
support.uk@hikvision.com

Hikvision Europe
T +31-23-5542770
saleseuro@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision France
T +33(0)1-85-330-444
info.fr@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Hong Kong
T +852-2151-1761