

HYU-1029

SF-IPD834ZW-4E

HYUNDAI

Vandal-resistant 4MP IP dome for outdoor use



- HYUNDAI Value Line IP Dome
- 4MP@20ips, H.265+/H.265
- ICR, StarLight 0.005 lux, Smart IR 30m
- Motorised optics 2.8 ~12 mm
- WDR 120dB, 3D-DNR, ROI
- MicroSD slot, RJ45, IP67, IK10, 3AXIS, 12V/PoE.



Reference / Model	HYU-1029 / SF-IPD834ZW-4E
4-megapixel 1/3" CMOS image sensor	
Resolution: 4MP (2560x1440), 1080P (1920x1080), 720P (1280x720), VGA (640x480), Q720P (640x360)	
H.265+, H.265, H.264+, H.264, H.264 and MJPEG video compression	
Stream 1: 4MP (20 fps), 1080P, 720P (25/30 fps)	
Stream 2: 720P, VGA, Q720P (25/30 fps)	
Day/Night mode with removable mechanical filter (ICR)	
0.005 lux F1.6 (colour), 0 lux IR On	
Smart IR: 30 meters (EXIR 2.0)	
2.8 ~ 12 mm motorised optics	
Angle of view: 102°~31°(H), 54°~17°(V), 123°~35°(D)	
Picture modes: BLC, WDR 120dB, 3D-DNR	
1 ROI zone fixed for main stream	

Vandal-resistant 4MP IP dome for outdoor use**Reference / Model****HYU-1029 / SF-IPD834ZW-4E**

Saturation, brightness, contrast, sharpness, gain and white balance adjustable via client software or web browser

MicroSD card slot for cards up to 256GB (card not included)

Network interface: RJ45 (10/100M) auto adaptive

Network Protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP™, SMTP, IGMP, 802.1X, QoS, IPv6, Bonjour, IPv4, UDP, SSL/TLS

Onvif, ISAPI support

Up to 32 users and 6 remote views

Compatible with IE, Chrome and Firefox browsers

Plug&Play connection with NVR NEXTGEN

Compatible with DDNS DEMES

Power supply: 12V DC (±25%) / PoE (802.3af)

Power consumption: 10W (12V) / 11.5W (PoE)

Operating Temperature -30°C ~ +60°C

Humidity: <95% (non-condensing)

IP67 degree of protection

Vandal protection IK10

Metal housing

Dimensions: Ø141 x 99.9 mm

Weight: 820 g

3AXIS: 0°~355°(PAN), 0°~70°(TILT), 0°~355°(ROTATION)