

HYU-960

HYU-960

HYUNDAI

HYUNDAI ColorView 4MP Outdoor IP Camera



- HYUNDAI ColorView IP Camera
- 4MP@25fps, H.265+/H.265
- Color 24/7, 0.0005 lux, white light 40m
- 2.8mm fixed lens
- WDR 130dB, 3D-DNR, ROI
- Perimeter protection and facial capture
- Motion detection 2.0
- Includes microphone
- MicroSD slot, Onvif, RJ45, IP67, 3AXIS, 12V/PoE



Reference / Model	HYU-960 / HYU-960
1/1.8" 4 Megapixel CMOS Image Sensor	
Resolution: 4MP (2688x1520), 1080P (1920x1080), 720P (1280x720), VGA (640x480), Q720P (640x360)	
Video compression H.265+, H.265, H.264+, H.264 and MJPEG	
Stream 1: 4MP, 1080P, 720P (25fps)	
Stream 2: VGA, Q720P (25fps)	
Stream 3: 1080P, 720P, VGA, Q720P (10fps)	
24h color mode	
0.0005 lux F1.0 (color, AGC On), 0 lux with white light On	
White lighting: 40 meters	
2.8mm fixed lens	
View Angle: 112°(H), 61°(V), 134°(D)	
Image modes: BLC, HLC, WDR 130dB, 3D-DNR	
1 fixed ROI zone for main and secondary streams	

HYUNDAI ColorView 4MP Outdoor IP Camera

Reference / Model	HYU-960 / HYU-960
	Image rotation, saturation, brightness, contrast, sharpness, white balance and gain control adjustable via client software or web browser
	Perimeter protection: Line crossing detection, intrusion detection, area entry/exit detection
	Face capture
	Motion detection 2.0: Deep learning-based motion detection 2.0 is enabled by default for all analogue channels, can classify people and vehicles and minimise false alarms caused by lights or objects such as leaves
	Includes microphone
	MicroSD card slot up to 256GB (card not included)
	Network interface: RJ45 (10/100M) self-adaptive
	Network Protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, ARP
	Compliant with ONVIF (S/G/T), ISAPI, SDK
	Up to 32 users and 6 simultaneous views
	Compatible with IE, Chrome and Firefox browsers
	Plug&Play connection with NEXTGEN NVR
	Compatible with DDNS DEMES
	Power: 12V DC ($\pm 25\%$) / PoE (802.3af)
	Consumption: 6W (12V) / 7.5W (PoE)
	Operating temperature $-30^{\circ}\text{C} \sim +60^{\circ}\text{C}$
	Humidity: <95% (non-condensing)
	Degree of protection IP67
	Dimensions: 78.8(W) x 78.6(H) x 215.2mm
	Weight: 695g
	3AXIS: $0^{\circ} \sim 360^{\circ}$ (PAN), $0^{\circ} \sim 75^{\circ}$ (TILT), $0^{\circ} \sim 360^{\circ}$ (Rotation)