

HYU-112N

HDCVI BULLET CAMERA, 2MP, MOTORIZED ZOOM & POSITIONER

HYUNDAI

HDCVI™



FEATURES

- 1080p HD resolution with Sony® CMOS sensor
- IR illumination up to 80 meters
- 5.1~51 mm varifocal lens with autofocus
- Transmission distance up to 300 (theoretical) meters
- BLC, Real WDR, ROI
- Positioner: 0°~250° (H), -10°~55° (V)
- Speed: 0,5°~15°/sec. (H), 0,5°~10°/sec. (V)
- 255 presets, 8 rounds, 4 patterns
- OSD menu, CVI video output
- IP66
- Surge protection

CAMERA

Image sensor	1/2,9" Sony® CMOS, 2 MP
Effective pixels	1920(H) x 1080(V)
Frames per second	PAL/NTSC: 25/30 fps @1080P
IR illumination	4 array led: 80 meters
Minimum illumination	0 lux IR ON
Video output	1 BNC (HDCVI / HDTVI / AHD)

LENS

Lens	5,1 ~ 51 mm
Focus mode	Automatic

FUNCTIONS

Day/night	Auto (ICR dual)
OSD menu	Supported
Backlight compensation	BLC, Real WDR
ROI	Supported

POSITIONER & TELEMETRY

Horizontal range	0° ~ 250°
Vertical range	-10° ~ +55°
Manual speed	0,5° ~ 15°/sec. horizontal / 0,5° ~ 10°/sec. vertical
Presets	255 presets (8 rounds, 4 patterns)

ELECTRICAL & ENVIRONMENTAL

Power supply	12V DC (±10%)
Transmission distance	Up to 300 meters (theoretical) via 75-3 coaxial cable
Protection	IP66

PHYSICAL FEATURES

Dimensions	225x185x94 mm
------------	---------------