

4 CHANNEL IP NVR WITH POE SWITCH X4



FEATURES

- Dual O/S
- H.265
- 4 IP camera inputs
- Input bandwidth: 40 Mbps
- Output bandwidth: 80 Mbps
- VGA (1080p) and HDMI (4K) output
- 2 way audio: 1 RCA in / 1 RCA out
- Recording resolution: 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF
- 8 MP live display
- 4 channel simultaneous playback @ 1080p
- 1 SATA port for 1 HDD up to 6TB (not included)
- RJ45 fast ethernet auto adaptive network interface
- Compatible with ONVIF
- Technology ANR
- Intelligent search for an efficient playback (for NEXTGEN IP cameras)
- Multiple VCA event supported of IP cameras
- Cloud P2P, DDNS DEMES, Push and zero channel
- 4 independent PoE ports incorporated (802.3af/at)
- Plug&Play connection with IP NEXTGEN cameras

SOFTWARE AND APPS

- HYUVMS and HYUCONNECT for Android and iOS
- HYU VMS client software
- Cloud P2P service: hyucloud.hyundai-security.es



VIDEO & AUDIO

IP input	4 channels
Audio input	1 RCA channel (2.0 Vp-p, 1kΩ)
Audio output	1 RCA channel (lineal, 1kΩ)
Input bandwidth	40 Mbps
Output bandwidth	80 Mbps
Video output	1 HDMI (3840x2160 /30Hz, 1920x1080P /60Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz), 1 VGA (1920x1080P /60Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz)

RECORDING

Video compression	H.265 / H.264 / H.264+
Resolution	8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF

DECODING

Display and playback resolution	8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF
Synchronous playback	4 channels @ 1080P

NETWORK

Network interface	1x RJ-45 (10/100M), auto-adaptive
Compatibility	Onvif, P2P, DDNS

STORAGE

SATA ports	1x SATA for 1 HDD (not included)
Capacity	Max. 6TB per HDD

AUXILIARY INTERFACE

USB	1x USB 2.0, 1x USB 3.0
-----	------------------------

POE

Interface	4x 100 Mbps independent PoE ports
Maximum consumption	≤40W
Supported standards	AF (15W), AT (30W)

ELECTRICAL & ENVIRONMENTAL

Power supply	48V DC
Consumption	≤10W (without HDD or PoE)
Working temperature	-10°C ~ +55°C
RH	10% ~ 90% RH

PHYSICAL FEATURES

Dimensions	315 x 240 x 48 mm
Weight	≤1 kg