



KEY FEATURES

- Fixed IP dome with IR of 40 m, for outdoors
- H.265/H.264
- 1/2,9" Sony® CMOS, 2 MP
- 2MP @25/30 fps
- Dual stream
- 2,7 ~ 13,5 mm motorized lens with autofocus
- ICR filter
- OSD, Digital WDR
- Audio: 1 in/out
- Onvif

HYU-302N HYU-302N


FIXED IP DOME WITH IR OF 40 M, FOR OUTDOORS

- 1/2,9 Sony® CMOS sensor, 2 MP
- Digital resolution: 1080P (1920x1080), 720P (1280x720), D1 (704x576), VGA (640x480), EGA (640x352), QVGA (320x240)
- H.265/H.264
- Stream 1: 1080P, 720P (1~25/30 fps)
- Stream 2: D1, VGA, EGA, QVGA (1~25/30 fps)
- Removable mechanical filter
- Smart IR: 3 array led, 40 meters
- Minimum illumination: 0,1 lux color F1.2 / 0,01 lux B/W F1.2
- 2,7~13,5 mm motorized lens with autofocus
- Audio: 1 in / 1 out
- OSD menu, digital WDR
- Audio: 1 in / 1 out
- Integration with other brands by Onvif 2.4
- Compatible with ZVR/NVR NEXTGEN via Onvif
- P2P intuitive with QR code
- Free Webserver and CMS
- Power supply: 12V DC, 400 mA
- PoE supported
- Working temperature: -10°C ~ +55°C
- IP66
- PVC and metal case
- Dimensions: Ø126,6 x 110,8 mm
- Reset button
- Waterproof cable

RELATED PRODUCTS



SAM-4145



SAM-4356