

CVBS HDCVI™

HDTVI AHD



FEATURES

- Up to 5MP with Sony CMOS sensor
- IR illumination up to 40 m
- 2,8 mm fixed lens
- Transmission distance 300 meters
- WB, AE, DNR, mirror mode
- OSD menu
- 4 in 1 output (DIP switch): CVBS @960H, CVI @4MP, TVI @5MP, AHD @5MP
- IP66
- 3AXIS with wiring hole

ACCESSORIES



HYU-332
Connection base

CAMERA

Image sensor	1/2,9 Sony® Exmor CMOS, 5 MP
Effective pixels	2560(H) x 1920(V)
Resolution	HDTVI 5MP (2560x1920) / 4MP (2560x1440) / 1080P (1920x1080)
	AHD 5MP (2560x1920) / 4MP (2560x1440) / 1080P (1920x1080)
	HDCVI 4MP (2560x1440) / 1080P (1920x1080)
	Analog 960H (960x576)
IR illumination	2 led array: 30 ~ 40 m
Minimum illumination	0,01 lux F1,2 (AGC On) / 0 lux IR ON
Video output	AHD, HD-CVI, HD-TVI, 1 BNC CVBS (DIP switch)

LENS

Lens	2,8 mm
------	--------

FUNCTIONS

Day/night	Auto (ICR), Color, B/W
OSD menu	Supported
White balance	Supported
Auto exposure	Supported
Noise reduction	DNR
Mirror mode	Supported

ELECTRICAL & ENVIRONMENTAL

Power supply	12V DC (±1V) /300 mA
Working temperature	-10°C ~ +55°C
RH	<85% HR
Transmission distance	Up to 300 m (theroretical) via 75-5 coaxial cable
Protection	IP66

PHYSICAL FEATURES

Case	PVC and metal
Dimensions	250 x 90 x 75 mm