



**8MP 12FPS P2P ONVIF**  
**HDCVI™ HDTV1 AHD CVBS**

## KEY FEATURES

- 8 channel 5 in 1 ZVR 8MP (7 ips) / 5 MP (12 fps) / 4 MP (15 fps) / 3MP (18 fps) / 1080P (25 fps) HDTV1/HDCVI/AHD/CVBS + 2 IP channels 6MP
- H.265+/H.265/H.264+/H.264
- Audio: 4 in / 1 out (2 way audio)
- Recording: 6MP (IP), 8MP/5MP/4MP/3MP (TVI), 1080P, 720P, WD1, 4CIF, VGA, CIF, QVGA, QCIF, full 1080P in all cameras
- BNC output at 4CIF
- HDMI (4K, 2K) and VGA (1080P) output
- Alarm: 8 in / 4 out
- 1 HDD SATA capacity
- RJ45 Gigabit
- Onvif, P2P, DDNS

## RELATED PRODUCTS



8 CHANNEL 5 IN 1 ZVR 8MP (7 IPS) / 5 MP (12 FPS) / 4 MP (15 FPS) / 3MP (18 FPS) / 1080P (25 FPS) HDTV1/HDCVI/AHD/CVBS + 2 IP CHANNELS 6MP

- 8 channels 5 in 1 ZVR, H.265+/H.265/H.264+/H.264
- 5 technologies: IP, HDCVI, HDTV1, AHD and CVBS
- H.265+ improves coding efficiency up to 70% and reduces video data storage costs
- 8 BNC inputs (coaxitron supported):
- HDCVI (2.0): 1080P/720P
- HDTV1 (4.0): 8MP/5MP/4MP/3MP/1080P/720P
- AHD: 1080P/720P
- CVBS: 960H
- 2 IP inputs at 6MP
- VGA (1080P) and HDMI (4K, 2K) output
- BNC auxiliary output up to 704x576
- Audio channels: 4 RCA in / 1 RCA out
- 2 way audio: via audio channel 1
- Display resolution: 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, WD1, 4CIF, VGA, CIF
- Recording resolution: 6MP (only IP), 8MP/5MP/4MP/3MP (only TVI), 1080P, 720P, WD1, 4CIF, VGA, CIF
- Stream 1: 8MP (7 fps), 5MP (12 fps), 4MP (15 fps), 3MP (18 fps), 1080P/720P/WD1/4CIF/VGA/CIF (25/30 fps)
- Stream 2: WD1/4CIF/CIF (25/30 fps)
- 8 channel simultaneous playback
- Multi-camera inverse playback
- Local playback speed up to x256 (forward and backward)
- Alarm channels: 8 in / 4 out
- 1 HDD SATA internal capacity up to 8TB (not included)
- Supports hard disk quota mode; allows assigning different capacities to different channels
- Graphical user interface (GUI) and one-button recording support (Wizard)
- Video quality diagnostic manual
- Search and playback by tags
- Lock and unlock log files
- Network interface: Ethernet RJ45 (10/100/1000M) auto-adaptive
- Network protocols: TCP/IP, PPPoE, DHCP, P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS
- Compatible with ONVIF
- Remote access up to 128 users
- Remote access via iPhone/iPad, Android
- Multi browser compatibility: Chrome, Firefox, Safari, IE
- P2P cloud, DDNS DEMES, Push and channel zero
- Connection: 1 USB 2.0, 1 USB 3.0, 1 RS485 half-duplex
- Power supply: 12V DC
- Consumption: ≤20W
- Working temperature: -10°C ~ +55°C
- RH: 10~90%
- Dimensions: 315 x 242 x 45 mm (desktop)
- Weight: ≤2 kg