

16 CHANNEL 5 IN 1 ZVR HDCVI/HDTVI/AHD/CVBS + 2 IP CHANNELS

KEY FEATURES

- 16 channel 5 in 1 ZVR HDCVI/HDTVI/AHD/CVBS + 2 IP channels
- H.265+/H265/H.264+/H264
- 2 way audio
- 16 channel playback
- Recording: 4MP (2 IP inputs), 4M-N, 3MP (channel 1 to 4, 15 fps, only TVI), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF (25 fps)
- HDMI and VGA output at 1080P
- 1 HDD SATA capacity
- Onvif, P2P, DDNS
- 2 USB
- 12V DC



H.265+ P2P Onvif HDCVI™
HDTVI AHD CVBS

RELATED PRODUCTS



HYU-385-2TB



- 16 channel 5 in 1 ZVR, H.265+/H265/H.264+/H.264
 - 5 technologies: IP, HDCVI, HDTV, AHD and CVBS
 - H.265+ coding efficiency and storage costs up to 70%
 - 16 BNC input (coaxitron supported):
 - HDCVI: 1080P/720P (telemetry control by coaxial cable of HDCVI cameras)
 - HDTV: 4MN / 3MP (channel 1 to 4) / 1080P / 720P (only on v3.0 cameras, not compatible with v1.0)
 - AHD: 1080P/720P
 - CVBS: 960H
 - 2 IP input up to 4MP
 - VGA and HDMI output up to 1920x1080
 - 2 way audio: 1 RCA in / 1 RCA out
 - Display resolution: 1080P, 1080N (960x1080), 720P, 960H, D1/4CIF, VGA, CIF
 - Recording resolution: 4M-N, 3MP (channels 1 to 4, only TVI mode), 4MP (only IP), 1080P, 1080N (960x1080), 720P, 960H, D1/4CIF, VGA, CIF
 - **- Stream 1 on 4M-N/3MP mode:**
 - Stream at 4MN/3MP: 4M-N, 3MP (15 fps)
 - - Stream 1 at 1080P mode:
 - Stream at 1080P: 1080P, 720P (15 fps), 960H, D1/4CIF, VGA, CIF (25/30 fps)
 - Stream at 720P: 720P, 960H, D1/4CIF, VGA, CIF (25/30 fps)
 - Stream 2: 960H, D1/4CIF (12 fps), CIF (25/30 fps)
 - 16 channel simultaneous playback
 - Multi-camera inverse playback
 - Local playback speed up to x256 (forward and backward)
 - 1 HDD SATA internal capacity up to 6TB (not included)
 - Supports hard disk quota mode; allows assigning different capacities to different channels
 - Graphical user interface (GUI) and one-button recording support (Wizard)
 - Video quality diagnostic manual
 - Search and playback by tags
 - Lock and unlock log files
 - Network interface: Ethernet RJ45 (10/100M) auto-adaptive
 - Network protocols: TCP/IP, PPPoE, DHCP, P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS
 - Compatible with ONVIF
 - Remote access up to 128 users
 - Remote access up to iPhone/iPad, Android
 - Multi browser compatibility: Chrome, Firefox, Safari, IE
 - P2P cloud, DDNS DEMES, Push and channel zero
 - Connections: 2 USB 2.0
 - Power supply: 12V DC
 - Consumption: ≤15W
 - Working temperature: -10°C ~ +55°C
 - RH: 10~90%
 - Dimensions: 285 x 210 x 45 mm (desktop)
- Weight: ≤1 kg