



PerformanceLine *IP67* *P2P*



KEY FEATURES

- IP vandal dome with IR of 30m, for outdoors, 2 MP
- H.265+/H.265/H.264+/H.264/MJPEG
- 1/2,8" CMOS, 2MP
- 1080P, 1,3MP, 720P, etc
- Mechanical filter
- 0,01 lux
- 2,8~12 mm (98°~34°) motorized lens with autofocus
- OSD, AGC, BLC, WDR digital, 3D-DNR, motion detection, privacy mask, fixed ROI
- MicroSD/SDHC/SDXC
- IP67, IK10

IP VANDAL DOME WITH IR OF 30M, FOR OUTDOORS, 2 MP

- 1/2,8" CMOS, 2MP
- Digital resolution: 1080P (1920x1080), 1,3MP (1280x960), 720P (1280x720), etc.
- H.265+/H.265/H.264+/H.264/MJPEG
- Stream 1: 1080P, 1,3MP, 720P (25/30 fps)
- Stream 2: 704x576 (25 fps), 704x480 (30 fps), 640x480, (25/30 fps), 352x288 (25 fps), 352x240 (30 fps), 320x240 (25/30 fps)
- Day/night mode with removable mechanical filter
- IR illumination: 30 meters
- Minimum illumination: 0,01 lux F1.2 color / 0,018 lux F1.6 color / 0 lux IR On
- 2,8 ~ 12 mm (98°~34°) motorized lens with autofocus
- OSD menu, AGC, BLC, WDR digital, 3D-DNR
- 1 fixed ROI
- motion detection and privacy mask
- Adjustment: brightness, saturation, contrast, sharpness mirror
- MicroSD/SDHC/SDXC (up to 128 GB)
- Network interface: RJ45 (10/100 Base-T)
- Network protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
- Compatible with ONVIF (Profile S, G), PSIA, CGI, ISAPI
- Plug&Play with NVR NEXTGEN connection
- Compatible with DDNS DEMES
- Power supply: 12V DC /10W (PoE 12W)
- PoE 802.3af supported
- Working temperature: -30°C ~ +50°C
- RH: 95% (without condensation)
- IP67
- IK10
- Metal case
- Dimensions: Ø141 x 99,9 mm
- Weight: 800 g
- 3AXIS: wall and ceiling installation
- Reset button
- Power supply is not included