



4Mn IP4k ONVIF HDCVI™
HDTV1 AHD CVBS

KEY FEATURES

- 32 channels 5 in 1 ZVR HDCVI/HDTV1/AHD/CVBS + 8 IP channels 6MP
- H.265+/H.265/H.264+/H.264
- Audio: 4 in / 1 out (2 way audio)
- Recording 6MP (IP), 4M-N (TVI, AHD, 15 fps), 3MP (channels 1 to 4, 15 fps, only TVI), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps)
- BNC output (4CIF)
- BNC output at D1/4CIF
- HDMI (4K, 2K) and VGA (1080P) output
- Alarm: 16 in / 4 out
- 4 HDD SATA capacity
- 1 eSATA

32 CHANNELS 5 IN 1 ZVR HDCVI/HDTV1/AHD/CVBS + 8 IP CHANNELS 6MP

- 32 channel 5 in 1 ZVR, H.265+/H.265/H.264+/H.264
- 5 technology: IP, HDCVI, HDTV1, AHD and CVBS analog
- H.265+ improves coding efficiency up to 70% and reduces data video storage costs
- 32 BNC input (coaxitron supported):
- HDCVI: 1080P/720P
- HDTV1: 4MN/3MP/1080P/720P
- AHD: 4MN/1080P/720P
- CVBS analog: 960H
- 8 IP inputs 6MP
- VGA (1080P) and HDMI (4K, 2K) output
- BNC auxiliary interface up to 704x576
- Audio channels: 4 RCA in / 1 RCA out
- 2 way audio: via audio channel 1
- Recording resolution: 6MP (only IP), 4M-N, 3MP (channels 1 to 4, only TVI), 1080P, 1080N (960x1080), 720P, 960H, D1/4CIF, VGA, CIF
- Stream 1 on 4M-N/3MP mode:
- Stream at 4MN/3MP: 4M-N, 3MP (15 fps)
- Stream 1 on 1080P mode:
- Stream at 1080P: 1080P, 720P (15 fps), 960H, D1/4CIF, VGA, CIF (25/30 fps)
- Stream at 720P: 720P, 960H, D1/4CIF, VGA, CIF (25/30 fps)
- Stream 2: 960H, D1/4CIF (12 fps), CIF (25/30 fps)
- 16 channel synchronized playback
- Alarm channels: 16 in / 4 out
- 4 HDD SATA capacity up to 8TB (not included)
- eSATA supported
- HDD Quota mode supported; allows you to assign different capabilities to different channels
- GUI and recording start support with a single key (Wizard)
- Video quality diagnosis
- Locking and unlocking log files
- Network interface Ethernet RJ45 (10/100/1000M) auto-adaptive
- Network protocols: TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS
- Compatible with ONVIF
- Remote access up to 128 users
- Remote access via iPhone/iPad, Android
- Multi browser compatibility: Chrome, Firefox, Safari, IE
- P2P cloud, DDNS DEMES, Push and zero channels
- Connections: 2x USB 2.0, 1x USB 3.0, 1x RS485 full duplex, 1x RS232
- Power supply: 100V ~ 240V AC
- Consumption: ≤45W (without HDD)
- Working temperature: -10°C ~ +55°C
- RH: 10~90%
- Dimensions: 440 x 390 x 70 mm (rack 19", 1.5U)
- Weight: ≤7 kg