



KEY FEATURES

- 8 channel IP NVR with POS function
- H.265/H.264+/H.264/MPEG4
- 8 channel playback @ 1080P
- Display up to 8MP
- Recording 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, 4CIF, etc
- Recording up to 80 Mbps
- VGA @ 1080P and HDMI @ 4K output
- 2 way audio
- Alarm: 4 in / 1 out
- 2 HDD SATA supported

FEATURES

- 8 channel IP NVR, H.265/H.264+/H.264/MPEG4
- Dual OS system
- ENABLED POS FUNCTION (up to 4 terminals)
- 1 channel LPR supported (Function performed by the LPR camera)
- Supports VCA events generated by cameras (motion detection, tripwire, intrusion, etc.)
- 8 IP camera input
- Bandwidth input: 80 Mbps
- Bandwidth output: 256 Mbps
- VGA (1080P) and HDMI (4K, 2K) video output
- 2 way audio: 1 RCA in / 1 RCA out
- Display resolution: 12MP, 8MP, 6MP, 5MP, 3MP, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF
- Recording resolution: 12MP, 8MP, 6MP, 5MP, 3MP, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF
- 8MP live display
- 8 channel at 1080P simultaneous playback, 4 channel 8MP
- Alarm channels: 4 in / 1 out
- Storage: 2 SATA ports up to 6TB (HDD not included)
- Network interface Ethernet RJ45 (10/100/1000M) auto-adaptive
- Compatible with ONVIF
- Tecnología ANR technology
- Intelligent search (for IP NEXTGEN cameras)
- Multiple VCA events supported of IP cameras
- P2P cloud, DDNS DEMES, Push and zero channel
- Plug&Play connection with IP NEXTGEN cameras
- Connections: 1 USB 2.0, 1 USB 3.0
- 8 independent ports incorporated on rear panel (100Mbps) PoE+ 802.3af/at
- PoE consumption: 120W
- Power supply: 100V ~ 240V AC
- Consumption with PoE: ≤180W
- Consumption without PoE: ≤15W (without PoE and HDD)
- Working temperature: -10°C ~ +55°C
- RH: 10~90%
- Dimensions: 380 x 290 x 45 mm
- Weight: ≤3 kg