

IP VANDAL BULLET CAMERA PERFORMANCE LINE WITH IR ILLUMINATION OF 50M, FOR OUTDOORS 6 MP



PerformanceLine **6MP** **IP67**
P2P 

KEY FEATURES

- IP vandal bullet camera Performance Line with IR illumination of 50m, for outdoors 6 MP
- H.265+/H.265/H.264/H.264+/MJPEG
- 1/2,9" CMOS of 6MP
- Digital resolution: 6MP, 5MP, 4MP, 1080P, 720P, 20FPS
- Mechanical filter
- 0,01 lux
- 2,8~12 mm (88°~27°) motorized lens with autofocus
- OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI
- Intelligent functions
- Facial detection

FEATURES 1/2,9" CMOS SENSOR, 6 MP- DIGITAL RESOLUTION: 6MP (3072X2048), 5MP (3072X1728), 4MP (2560X1440), 1080P (1920X1080), 720P (1280X720), ETC.- H.265+/H.265/H.264+/H.264/MJPEG- STREAM 1: 6MP/5MP (20 FPS), 4MP/1080P/720P (25 FPS)- STREAM 2: VGA/QVGA (25 FPS)- STREAM 3: 720P/VGA/CIF (25 FPS)- DAY/NIGHT MODE WITH REMOVABLE MECHANICAL FILTER- IR ILLUMINATION: 50 METERS- MINIMUM ILLUMINATION: 0,01 LUX F1.2 COLOR / 0,018 LUX F1.6 COLOR / 0 LUX IR ON- 2,8 ~ 12 MM (88°~27°) MOTORIZED LENS WITH AUTOFOCUS- OSD MENU, AGC, BLC, REAL WDR 120DB, 3D-DNR- 1X ROI STREAM 1 AND STREAM 2- MOTION DETECTION AND PRIVACY MASK- ADJUSTMENT: BRIGHTNESS, SATURATION, CONTRAST, SHARPNESS, MIRROR MODE, IMAGE ROTATION

- IVS: Tripwire, intrusion detection- Facial detection- 2 way audio- Alarm: 1 in / 1 out- MicroSD/SDHC/SDXC card slot up to 128GB (card is not included)- Network interface: RJ45 (10/100 Base-T) - Network protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour- Compatible with ONVIF (profile S/G), PSIA, CGI, ISAPI- Plug&Play with NVR NEXTGEN- Compatible with DDNS DEMES- Power supply: 12V DC, max 14,5W- PoE+ 802.3at supported (42,5V ~ 57V CC; 0,5A ~ 0,3A; max. 18W)- Working temperature -30°C ~ +60°C- RH: <95%, without condensation- IP67- IK10- Metal case- 3AXIS bracket with space for connections- Power supply is not included- Reset button