

IP STARLIGHT MOTORIZED DOME OF 100°/SEC



STARLIGHT **IP66** **2MP** Onvif

KEY FEATURES

- IP StarLight motorized dome of 100°/sec
- with Smart IR 20m vandal protection for outdoors
- H.265+/ H.265/ H.264+/ H.264/ MJPEG
- 1/3" CMOS, 2MP
- Triple Stream
- Digital resolution of 2MP@25FPS
- ICR filter
- 0,005/0,001 lux
- 2,8 ~ 12 mm (109°~34°) motorized lens
- 16X digital zoom
- OSD, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, EIS, 2 ROI per stream, motion detection, 24 privacy mask
- IVS
- 2 way audio
- 300 presets
- MicroSD/SDHC/SDXC
- Onvif, PSIA, CGI
- IP66, IK10
- 12V DC
- PoE



Key features

- 1/3" CMOS sensor, progressive scan
- H.265+, H.265, H.264+, H.264, MJPEG
- 1920x1080@25fps
- Triple Stream
- IR range up to 20 meters
- 4X optical zoom
- 16X digital zoom
- 3DDNR
- Real WDR 120dB
- Suitable for outdoors (IP66)
- Vandal protection (IK10)
- PoE supported (Power over Ethernet)

SPECS

- 1/3" CMOS sensor, 2 MP
- Digital resolution: 1080P (1920x1080), 1,3MP (1280x960), 720P (1280x720), etc.
- H.265+/H.265/H.264+/H.264/MJPEG
- Stream 1: 1080P/1,3MP/720P (25 fps)
- Stream 2: D1/VGA/CIF (25 fps)
- Stream 3: 720P/D1/VGA/CIF (25 fps)
- Day/night mode with removable mechanical filter
- Smart IR: 20 meters
- Minimum illumination: 0,005 lux F1.6 color / 0,001 lux F1.6 B/W
- 4X optical zoom: 2,8 ~ 12 mm (109° ~ 34°)
- Zoom speed of 2 sec.
- Focus mode: auto, semiauto, manual
- 16X digital zoom
- OSD menu
- Auto/manual gain control
- White balance: Auto, manual, ATW (autotracking), indoor, light, sodium lamp
- Backlight compensation (BLC, HLC)
- Real WDR 120dB
- 3D-DNR
- EIS
- Regional exposure, regional focus
- 2 fixed ROI per stream
- Motion detection
- 24 programmable privacy mask
- IVS: intrusion, tripwire, entry area detection, exit area detection, deleting object detection, unattended luggage detection, audio exception detection, facial detección
- ANR and dual VCA
- Horizontal positioner: 0° ~ 330°
- Vertical positioner: 0° ~ 90°

- Manual speed: 0,1° ~ 100°/sec. (H), 0,1° ~ 100°/sec. (V)
- Preset speed: 100°/sec. (H), 100°/sec. (V)
- 300 presets
- Proportional zoom
- Audio: 1 in / 1 out
- MicroSD/SDHC/SDXC card slot up to 256GB (card is not included)
- Network interface: RJ45 (10/100 Base-T)
- Network protocols: IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE, Bonjour
- Compatible with ONVIF, ISAPI and CGI
- Up to 20 simultaneous users
- Web browser supported: IE 8~11, Chrome 31.0~44, Firefox 30.0~51
- Power supply: 12V DC, max 12W
- PoE 802.3af supported
- Working temperature -20°C ~ +60°C
- RH: <90%, without condensation
- IP66
- IK10
- Aluminum, polycarbonate and plastic case
- Dimensions: Ø130,7 x 101,7 mm
- Weight: 530 g
- Power supply is not included