

WiFi IP DOME WITH IR OF 30M, FOR OUTDOORS , 2 MP



KEY FEATURES

- WiFi IP dome with IR of 30m, for outdoors , 2 MP
- H.265+/H.265/H.264+/H.264//MJPEG
- 1/2,8" CMOS, 2MP
- Dual Stream
- Mechanical filter
- 0,028 lux.2,8 mm lens (114°)
- OSD, AGC, 3D-DNR, BLC, digital WDR, privacy mask, ROI
- Microphone incorporated
- MicroSD/SDHC/SDXC
- IP66

FEATURES

- 1/2,8" CMOS sensor, 2 MP
- Resolution: 1920x1080 at 25 fps
- 2,8 mm lens
- WiFi connectivity
- H.265+/H.265/H.264+/H.264
- 3D digital noise reduction
- Microphone incorporated (mono sound)
- IP66

SPECS

- 1/2,8" CMOS sensor, 2 MP
- Digital resolution: 1080P (1920x1080), 1,3MP (1280x960), 720P (1280x720), etc.
- H.265+/H.265/H.264+/H.264/MJPEG
- Stream 1: 1080P, 1,3MP, 720P (25 fps)
- Stream 2: 640x480, 640x360, 320x240 (25 fps)
- Day/night mode with removable mechanical filter
- IR illumination: 30 meters
- Minimum illumination: 0,028 lux F2.0 color / 0 lux IR On
- 2,8 mm lens
- Viewing angle: 114°H and 62°V
- Automatic gain control
- Backlight compensation
- Digital WDR
- 3D digital noise reduction
- Privacy mask, mirror, watermark
- 1 ROI on main stream
- Adjustment: brightness, saturation, contrast and sharpness via client software and web browser
- Microphone incorporated with mono sound
- Reset button
- MicroSD/SDHC/SDXC up to 128GB (card is not included)
- Network interface: RJ45 (10/100M) autoadaptive
- Network protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, QoS, IPv6, UDP, Bonjour
- WiFi 802.11b/g/n at 2,4GHz with WEP security, WPA/WPA2, WPAPSK/WPA-PSK2 and WPS
- WiFi range up to 50 meters in open field
- Compatible with ONVIF (Profile S/G), ISAPI
- Plug&Play with NVR NEXTGEN
- Compatible with DDNS DEMES
- IP66
- Power supply: 12V DC, max 4,8W
- Working temperature: 30°C ~ +60°C