



**2MP HDCVI™ HDTVI AHD
CVBS**

KEY FEATURES

- 4 in 1 dome PRO series with IR illumination of 20~30 m for outdoors
- 1/2,9" CMOS, 2MP at 1080P
- 4 in 1 video output via DIP switch
- 2,8 ~ 12 mm varifocal lens
- ICR filter
- OSD, AWB, AGC, 2D-DNR, BLC, WDR digital
- IP65
- Lightning-proof
- 3AXIS
- 12V DC

HYU-702 HYU-702

4 IN 1 DOME PRO SERIES WITH IR ILLUMINATION OF 20~30 M FOR OUTDOORS

FEATURES

- 2MP CMOS
- 1080P at 25 frames per second
- 2,8 ~ 12 mm varifocal lens
- OSD control menu via coaxial cable (UTC)
- AWB, AGC, BLC, 2DDNR
- Digital WDR
- Lightningproof
- IP65

SPECS

- 1/2,9" CMOS, 2 MP
- Digital resolution: 1080P (1920x1080)
- 4 in 1 video output via DIP switch (HDCVI, HDTVI, AHD, CVBS)
- 0,02 lux F1.2 (color) / 0 lux IR On
- Removable mechanical filter
- Smart IR: 18 leds array, 20~30 meters
- 2,8 ~ 12 mm varifocal lens
- OSD via coaxial (only on CVI mode, 300 m range, not compatible with NEXTGEN ZVR)
- White balance: Auto, ATW, Indoor, Outdoor, Manual
- Automatic Gain control
- BLC
- Digital WDR
- 2D noise reduction
- Working temperature 20°C ~ +60°C
- RH: 10% ~ 90%
- IP65
- Lightningproof
- PVC and metal case
- Power supply: 12V DC (±10%)
- Consumption: <5W
- Dimensions: Ø119 x 98 (Al) mm
- 3AXIS: wall and ceiling installation