

# IM1640PAG

## Surface mount contact, armoured cable, NFA2P

### Commercial surface mount contact

---

The IM1640 series commercial surface mount contacts are specifically designed to work on metal frames. The contacts can be used in harsh environments. Special version with armoured cable and including junction box is available.



### Details

---

- Designed for use in harsh environments
- Magnet specifically designed to work on metal frames
- Tamper loop
- Version with armoured cable

# IM1640PAG

## Surface mount contact, armoured cable, NFA2P

### Technical specifications

---

#### General

Application type	Surface mount
Contact type	NC
Connectivity	4 wires, 60 cm (armoured cable)

#### Wired / wireless

Wired-wireless	Wired
Operating gap	25 mm

#### Electrical

Voltage	max. 48 VDC
---------	-------------

#### Physical

Physical dimensions	72 x 23 x 19 mm (W x H x D)
Dimensions magnet	23 x 72 mm
Dimensions contact / sensor	23 x 72 mm
Colour	White

#### Environmental

Operating temperature	-10 to +55°C
-----------------------	--------------



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](https://firesecurityproducts.com) online or contact your sales representative.

Last updated on 5 May 2023 - 9:53